


MANUAL TRAFFIC SPIKES



MODEL 11320 3 Ft. / 11620 6 Ft. Rated 20,000 lbs. per single axle load 1/4" Steel Top Plate

3 Ft. In-Ground Spike Sections

11320P Powder Coated Red

11320C Corrosion Resistant* Red

6 Ft. In-Ground Spike Sections

11620P Powder Coated Red

11620C Corrosion Resistant* Red



Heavy Duty

MODEL 11340 3 Ft. / 11640 6 Ft. Rated 40,000 lbs. per single axle load 3/8" Steel Top Plate

3 Ft. In-Ground Spike Sections

11340P Powder Coated Red

11340C Corrosion Resistant* Red

6 Ft. In-Ground Spike Sections

11640P Powder Coated Red

11640C Corrosion Resistant* Red

*Hot Dipped Galvanized - ASTM A153/A 153M

COBRA™ EZ Install

The COBRA™ EZ Install Spikes can be used in all commercial and residential applications. The beauty behind this product is it can be installed in less than 3 hours, saving you both time and money!

Features & Benefits

- Rapid Installation (Less than 3 hours)
- Heavy-Duty Steel Construction
- Counter Balanced System
- Reliable Zinc Plated Moving Parts
- Positive Stop Eliminates Wear
- Specially Engineered Curved Teeth with Fish-Hook Disabler
- Built-In Latch Down Device
- Sound Dampeners to Decrease Noise Level
- Designed Top-Down for Easy Maintenance
- Modular Style For Design Flexibility
- Conditioned for Heater Cable System
- Restricts Tire Damage to Wrong Way Traffic
- One Year Limited Warranty

SAFETY REQUIREMENTS

- ⇒ Maximum 5 mph
- ⇒ Tires must pass over the unit so that the tire is parallel to the teeth and not at an angle
- ⇒ Warning Signs Required
- ⇒ Locating & installing a traffic spike system incorrectly or not using warning signs voids any warranty

