



# MANUAL TRAFFIC SPIKES



## COBRA™ Surface Mount

The COBRA™ Surface Mount Spikes can be used in all commercial and residential applications. This product is easy to install on asphalt and concrete surfaces. The COBRA™ unit also acts as a speed bump.

**MODEL 12300 3 Ft. Traffic Spike Sections**  
Rated 15,000 lbs. per single axle load  
1/4" Steel Top Plate

- 12300P Powder Coated Red
- 12300C Corrosion Resistant\* Red
- 12300Y Powder Coated Yellow
- 12300CY Corrosion Resistant\* Yellow

### 7" End Bevels - Set of 2

- 12300E Corrosion Resistant\* Red
- 12300EY Corrosion Resistant\* Yellow



**MODEL 12360 3 Ft. Traffic Spike Sections**  
Rated 36,000 lbs. per single axle load  
3/8" Top Plate

- 12360P Powder Coated Red
- 12360C Corrosion Resistant\* Red

### 7" End Bevels - Set of 2

- 12360E Corrosion Resistant\* Red

\*Hot Dipped Galvanized - ASTM A153/A 153M

### Features & Benefits

- Heavy-Duty Steel Construction
- Counter Balanced & Spring Loaded System
- Reliable Zinc Plated Moving Parts
- Positive Stop Eliminates Wear
- Specially Engineered Curved Teeth with Fish-Hook Disabler
- Stainless Steel Hardware
- Built-In Latch Down Device
- Designed Top-Down for Easy Maintenance
- Modular Style For Design Flexibility
- Restricts Tire Damage to Wrong Way Traffic
- One Year Limited Warranty

### SAFETY REQUIREMENTS

- ⇒ Maximum 5 mph
- ⇒ Tires must pass over the unit so that the tire is parallel to the teeth and not at an angle
- ⇒ Warning Signs Required
- ⇒ Locating & installing a traffic spike system incorrectly or not using warning signs voids any warranty

